

Attorney Docket No.: 944-3.79
Serial No.: 09/912,227

In the claims: The claims are as follows.

1. (Previously presented) A method for use by a second communication device in deciding whether to perform link adaptation for communication from a first communication device to the second communication device, the link adaptation resulting in a change in coding or modulation or both, the method comprising the steps of:

examining a signal received from the first communication device and so providing a first indication of the quality of the signal as received by the second communication device;

recording the first indication of the quality of the signal as received by the second communication device;

providing a second indication of the quality of the signal;
and

deciding to perform link adaptation based on the first and second indication of the quality of the signal.

2. (Previously presented) The method of claim 1, wherein the first indication of the quality of the signal as received by the second communication device is either an SIR estimate, or an FER or BLER or corresponding statistic collected over a predetermined time period.

3. (Previously presented) The method of claim 1, wherein the second indication of the quality of the signal as received by the second communication device is either an SIR target value, or a changed SIR target value.

4. (Original) The method of claim 3, wherein the decision to perform link adaptation is based on whether the SIR target is to be changed to a value that is within some predetermined margin of

Attorney Docket No.: 944-3.79
Serial No.: 09/912,227

a predetermined maximum or minimum SIR target.

5. (Original) The method of claim 3, wherein a succession of SIR target change commands are recorded, and further wherein the decision to perform link adaptation is based on whether a predetermined number of consecutive SIR target change commands are all either to increase the SIR target or to decrease the SIR target.

6. (Currently amended) The method of claim 3, wherein a succession of SIR target change commands are recorded, and further wherein the decision to perform link adaptation is based on whether a predetermined fraction of a predetermined number of the SIR target change commands are either to increase the SIR target or to decrease the SIR target.

7. (Previously presented) The method of claim 1, wherein the first communication device is selected from the group consisting of a mobile station and a base station and the second communication device is the other device in the group consisting of the mobile station and the base station.

Claim 8 is canceled.

Claim 9 is canceled.

10. (Currently amended) The method of claim 1, wherein the signal for which either the first or second indication of the quality of the signal as received by the second communication device ~~is~~ are used as a basis for a link adaptation decision is different from, but associated with, the signal for which the link adaptation decision is made.

11. (Currently amended) An apparatus for use by a second

Attorney Docket No.: 944-3.79
Serial No.: 09/912,227

communication device in deciding whether to perform link adaptation for communication from a first communication device to the second communication device, the link adaptation resulting in a change in coding or modulation or both, ~~the second communication device examining a signal received from the first communication device and providing a first indication of the quality of the signal as received by the second communication device,~~ the apparatus comprising:

means for examining a signal received from the first communication device and so providing a first indication of the quality of the signal as received by the second communication device;

means for recording the first indication of the quality of the signal as received by the second communication device;

means for providing a second indication of the quality of the signal; and

means for deciding to perform link adaptation based on the first and second indication of the quality of the signal.

12. (Currently amended) The apparatus of claim 11, wherein the first indication of the quality of the signal as received by the second communication device is either an SIR estimate, or an FER or BLER or corresponding statistic collected over a predetermined time period.

13. (Currently amended) The apparatus of claim 11, wherein the second indication of the quality of the signal as received by the second communication device is either an SIR target value, or a changed SIR target value.

14. (Original) The apparatus of claim 13, wherein the decision to perform link adaptation is based on whether the SIR target is

Attorney Docket No.: 944-3.79
Serial No.: 09/912,227

to be changed to a value that is within some predetermined margin of a predetermined maximum or minimum SIR target.

15. (Original) The apparatus of claim 13, wherein a succession of SIR target change commands are recorded, and further wherein the decision to perform link adaptation is based on whether a predetermined number of consecutive SIR target change commands are all either to increase the SIR target or to decrease the SIR target.

16. (Currently amended) The apparatus of claim 13, wherein a succession of SIR target change commands are recorded, and further wherein the decision to perform link adaptation is based on whether a predetermined fraction of a predetermined number of the SIR target change commands are either to increase the SIR target or to decrease the SIR target.

Claim 17 is canceled.

Claim 18 is canceled.

Claim 19 is canceled.

20. (Currently amended) The ~~method~~ apparatus of claim 11, wherein the signal for which the first and second indication of the quality of the signal as received by the second communication device ~~is~~ are used as a basis for a link adaptation decision is different from, but associated with, the signal for which the link adaptation decision is made.

21. (Previously presented) The method of claim 1, wherein the link adaptation decision is based on a succession of signal quality indicators provided by a function that generates an increase or decrease in signal quality indicator depending on

Attorney Docket No.: 944-3.79
Serial No.: 09/912,227

whether or not a frame is correctly received.

22. (Currently amended) The apparatus of claim 11, wherein the link adaptation decision is based on a succession of signal quality indicators provided by a function that generates an increase or decrease in signal quality indicator depending on whether or not a frame is correctly received, and wherein both the first and second ~~quality indicators~~ indications of the quality of the signal are such quality indicators.

23. (Previously presented) A method of deciding whether to perform link adaptation for communication from a first communication device to a second communication device, the link adaptation resulting in a change in coding or modulation or both, the second communication device examining a signal received from the first communication device and providing a first indication of the quality of the signal as received by the second communication device, the method comprising the steps of:

recording the first indication of the quality of the signal as received by the second communication device;

providing a second indication of the quality of the signal;
and

deciding to perform link adaptation based on the first and second indication of the quality of the signal;

wherein the second indication of the quality of the signal as received by the second communication device is either an SIR target value, a changed SIR target value, an ACK/NACK signal, or a signal derived from a series of consecutive ACK/NACK signals;

and further wherein the decision to perform link adaptation is based on whether the SIR target is to be changed to a value that is within some predetermined margin of a predetermined maximum or minimum SIR target.

Attorney Docket No.: 944-3.79
Serial No.: 09/912,227

24. (Previously presented) A method of deciding whether to perform link adaptation for communication from a first communication device to a second communication device, the link adaptation resulting in a change in coding or modulation or both, the second communication device examining a signal received from the first communication device and providing a first indication of the quality of the signal as received by the second communication device, the method comprising the steps of:

recording the first indication of the quality of the signal as received by the second communication device;

providing a second indication of the quality of the signal;
and

deciding to perform link adaptation based on the first and second indication of the quality of the signal;

wherein the second indication of the quality of the signal as received by the second communication device is either an SIR target value, a changed SIR target value, an ACK/NACK signal, or a signal derived from a series of consecutive ACK/NACK signals;

and further wherein a succession of SIR target change commands are recorded, and further wherein the decision to perform link adaptation is based on whether a predetermined number of consecutive SIR target change commands are all either to increase the SIR target or to decrease the SIR target.

25. (Currently amended) A method of deciding whether to perform link adaptation for communication from a first communication device to a second communication device, the link adaptation resulting in a change in coding or modulation or both, the second communication device examining a signal received from the first communication device and providing a first indication of the quality of the signal as received by the second communication device, the method comprising the steps of:

Attorney Docket No.: 944-3.79
Serial No.: 09/912,227

recording the first indication of the quality of the signal
as received by the second communication device;

providing a second indication of the quality of the signal;
and

deciding to perform link adaptation based on the first and
second indication of the quality of the signal;

wherein the second indication of the quality of the signal
as received by the second communication device is either an SIR
target value, a changed SIR target value, an ACK/NACK signal, or
a signal derived from a series of consecutive ACK/NACK signals;

and further wherein a succession of SIR target change
commands are recorded, and wherein the decision to perform link
adaptation is based on whether a predetermined fraction of a
predetermined number of the SIR target change commands are either
to increase the SIR target or to decrease the SIR target.

26. (Previously presented) A method of deciding whether to
perform link adaptation for communication from a first
communication device to a second communication device, the link
adaptation resulting in a change in coding or modulation or both,
the second communication device examining a signal received from
the first communication device and providing a first indication
of the quality of the signal as received by the second
communication device, the method comprising the steps of:

recording the first indication of the quality of the signal
as received by the second communication device;

providing a second indication of the quality of the signal;
and

deciding to perform link adaptation based on the first and
second indication of the quality of the signal;

Attorney Docket No.: 944-3.79
Serial No.: 09/912,227

wherein the link adaptation decision is based on a succession of signal quality indicators provided by a function that generates an increase or decrease in signal quality indicator depending on whether or not a frame is correctly received.

27. (Previously presented) An apparatus for deciding whether to perform link adaptation for communication from a first communication device to a second communication device, the link adaptation resulting in a change in coding or modulation or both, the second communication device examining a signal received from the first communication device and providing a first indication of the quality of the signal as received by the second communication device, the apparatus comprising:

means for recording the first indication of the quality of the signal as received by the second communication device;

means for providing a second indication of the quality of the signal; and

means for deciding to perform link adaptation based on the first and second indication of the quality of the signal;

wherein the second indication of the quality of the signal as received by the second communication device is either an SIR target value, a changed SIR target value, an ACK/NACK signal, or a signal derived from a series of consecutive ACK/NACK signals; and

wherein the decision to perform link adaptation is based on whether the SIR target is to be changed to a value that is within some predetermined margin of a predetermined maximum or minimum SIR target.

28. (Previously presented) An apparatus for deciding whether to perform link adaptation for communication from a first

Attorney Docket No.: 944-3,79
Serial No.: 09/912,227

communication device to a second communication device, the link adaptation resulting in a change in coding or modulation or both, the second communication device examining a signal received from the first communication device and providing a first indication of the quality of the signal as received by the second communication device, the apparatus comprising:

means for recording the first indication of the quality of the signal as received by the second communication device;

means for providing a second indication of the quality of the signal; and

means for deciding to perform link adaptation based on the first and second indication of the quality of the signal;

wherein the second indication of the quality of the signal as received by the second communication device is either an SIR target value, a changed SIR target value, an ACK/NACK signal, or a signal derived from a series of consecutive ACK/NACK signals; and

wherein a succession of SIR target change commands are recorded, and further wherein the decision to perform link adaptation is based on whether a predetermined number of consecutive SIR target change commands are all either to increase the SIR target or to decrease the SIR target.

29. (Currently amended) An apparatus for deciding whether to perform link adaptation for communication from a first communication device to a second communication device, the link adaptation resulting in a change in coding or modulation or both, the second communication device examining a signal received from the first communication device and providing a first indication of the quality of the signal as received by the second communication device, the apparatus comprising:

Attorney Docket No.: 944-3.79
Serial No.: 09/912,227

means for recording the first indication of the quality of the signal as received by the second communication device;

means for providing a second indication of the quality of the signal; and

means for deciding to perform link adaptation based on the first and second indication of the quality of the signal;

wherein the second indication of the quality of the signal as received by the second communication device is either an SIR target value, a changed SIR target value, an ACK/NACK signal, or a signal derived from a series of consecutive ACK/NACK signals; and

wherein a succession of SIR target change commands are recorded, and further wherein the decision to perform link adaptation is based on whether a predetermined fraction of a predetermined number of the SIR target change commands are either to increase the SIR target or to decrease the SIR target.

30. (Currently amended) An apparatus for deciding whether to perform link adaptation for communication from a first communication device to a second communication device, the link adaptation resulting in a change in coding or modulation or both, the second communication device examining a signal received from the first communication device and providing a first indication of the quality of the signal as received by the second communication device, the apparatus comprising:

means for recording the first indication of the quality of the signal as received by the second communication device;

means for providing a second indication of the quality of the signal; and

means for deciding to perform link adaptation based on the first and second indication of the quality of the signal;

Attorney Docket No.: 944-3.79
Serial No.: 09/912,227

wherein the link adaptation decision is based on a succession of signal quality indicators provided by a function that generates an increase or decrease in signal quality indicator depending on whether or not a frame is correctly received, and wherein both the first and second ~~quality indicators~~ indications of the quality of the signal are such quality indicators.

31. (Currently amended) A system, comprising:

- a first communication device;
- a second communication device configured so as to be able to communicate with the first communication device; and
- a controlling entity for controlling the second communication device in communicating with the first communication device;

wherein the second communication device includes an apparatus for use in deciding whether to perform link adaptation for communications from the first communication device to the second communication device, the link adaptation resulting in a change in coding or modulation or both, ~~the second communication device examining a signal received from the first communication device and providing a first indication of the quality of the signal as received by the second communication device, the~~ apparatus comprising:

means for examining a signal received from the first communication device and so providing a first indication of the quality of the signal as received by the second communication device;

means for recording the first indication of the quality of the signal as received by the second communication device;

JUL-15-2005 10:27

WARE FRESSOLA

P.14/19

Attorney Docket No.: 944-3.79
Serial No.: 09/912,227

means for providing a second indication of the quality of
the signal; and

means for deciding to perform link adaptation based on the
first and second indication of the quality of the signal.